



DECLARATION OF PREFORMANCE

Nº 015-DoP-2014

1. Unique identification name and code of the product:

BRIK-CEN MS-AQUA

Lot: see packaging

2. Name and contact address of manufacturer:

INDUSTRIAS QUÍMICAS DEL ADHESIVO S.A., with head office:
C/ Valdelacueva s/n, 28880 Meco(Madrid)

3. Intended use:

Sealant for non-structural use in joints in buildings and pedestrian walkways.

Product: sealant for facade elements

Intended use : Sealant for interior applications

Intended use : Sealant for exterior applications

Product: joints sealant

Intended use : Sealant for glazing applications

4. Systems of assessment and verification of constancy of performance:

System of assessment (EVCP) : 3

System of assessment (EVCP) : 4 (reaction to fire)

5. Harmonised standard:

EN 15651-1:2012

EN 15651-2:2012

Notified Inspection Agency:

TECNALIA, registered inspection agency nº 1292, made initial tests for evaluation system EVCP 3 of this product.



6. Declared performance

Product: sealant for facade elements

Intended use : sealant for exterior applications

ESSENTIAL CHARACTERISTICS	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to fire EN 13501-1 :2007+A1	Class F	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	Information in MSDS	
Water tightness and air tightness		
Resistance to flow EN ISO 7390	≤3 mm / PASS	
Loss of volume EN ISO 10563	≤10% / PASS	
Tensile properties (i.e. deformation): at maintained extension after water immersion at 23 °C (plastic) EN ISO 10591	PASS	
Durability	PASS	

Product: sealant for facade elements

Intended use : sealant for interior applications

ESSENTIAL CHARACTERISTICS	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to fire EN 13501-1 :2007+A1	Class F	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	Information in MSDS	
Water tightness and air tightness		
Resistance to flow EN ISO 7390	≤5 mm / PASS	
Loss of volume EN ISO 10563	≤45% / PASS	
Tensile properties (i.e. elongation): at break at 23 °C EN ISO 8339	≥25%/PASS	
Durability	PASS	

Product: joint sealant


Intended use : sealant for glazing applications

ESSENTIAL CHARACTERISTICS	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to fire EN 13501-1 :2007+A1	Class F	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	Information in MSDS	
Water tightness and air tightness		
Resistance to flow EN ISO 7390	≤3 mm / PASS	
Loss of volume EN ISO 10563	≤10% / PASS	
Adhesion/cohesion properties after exposure to heat wáter and artificial light EN ISO 11431	NF /PASA	
Elastic recovery EN ISO 7389	≥40%	
Durability	PASS	

The performance of the product identified in points 1 is in conformity with the declared performance in point 6.

This declaration of performance is issued in compliance with EU Regulation (EU): n° 305/211 of March 9/2011 under the sole responsibility of manufacturer declared in point 2

7. Signature



Lucio Martinez Rodriguez

8. Place and date of issue

Meco, 18 november 2014.